

## MODEL CSJ

### INTERMITTENT-MOTION VERTICAL PACKAGING MACHINE

Description	Unit of measurement	Technical data
<b>Numbers of line</b>	--	1-3
<b>Dimensions WxHxD</b>	mm	Refer to the layout
<b>Maximum number of stick (Speed)*</b>	(Stick/min)	Until 180
<b>Reel*</b>	mm	Width Dim. Max 250
		Diameter Ext. 500
		Diameter Int. 76 (3")
<b>Sachet dimension*</b>	mm	Width 11-40
		Length 60-180
<b>Maximum sealing temperature *</b>	°C	220-240
<b>Storage ambient temperature</b>	°C	-25 °C e +55°C < 70°C (for period < 24h)
<b>Alimentation type</b>	--	TN-S/TT
<b>Electric voltage</b>	VAC	400 (USA 440V)
<b>Number of phases</b>	--	3+N+PE
<b>Frequency</b>	Hz	50 (USA 60Hz)
<b>Minimum and maximum power supply cable section</b>	mm <sup>2</sup>	4 - 6
<b>Maximum short circuit current (I<sub>cc</sub>)</b>	kA	10
<b>Maximum ground resistance impedance upstream of the machine</b>	Ω	166
<b>Current leakage to earth</b>	mA	<150mA
<b>Electromagnetic environment</b>	--	Type A (Industrial)
<b>Pneumatic circuit fluid</b>	--	Dry air
<b>Pneumatic circuit pressure</b>	bar	6
<b>Pipe connection diameter</b>	mm	10 -14
<b>Noise</b>	dBA	Lpa=76.1dbA CLpCpeack=81.5dbA

\* The data listed above are only indicative. OMAG reserves the right to redefine these data according to the specific project.